

## MACRAMÉ: LEAF/ FEATHER



## WHAT YOU NEED

- . MACRAME CORD (COTTON)
  - SINGLE STRAND GIVES A SMOOTHER FINISH THAN 4 PLY AND LESS UNTWISTING AT THE END (4 PLY IS WHAT'S IN THE IMAGES)
  - I'VE USED A CONTRASTING COLOUR FOR FILLER (WHITE)
     AND WORKING (GREEN) CORDS JUST SO IT SHOWS UP
     MORE EASILY FOR YOU.
  - $\circ$  I'D RECOMMEND DOING THE SAME COLOUR FOR BOTH.
- BULLDOG CLIP (TO SECURE YOUR CORD IN PLACE)
- SCISSORS
- BRUSH/ COMB FOR FRAYING


## CORD LENGTHS

WRAP THE MACRAME CORD AROUND YOUR FOREARM ONCE TO MAKE THE LENGTH OF YOUR FILLER CORD (MINE IS AROUND 60CM)


- IN THE IMAGE THIS IS THE WHITE CORD.

THEN WRAP YOUR MACRAME CORD AROUND YOUR FOREARM 10 TIMES. CUT AT THE TOP AND THE BOTTOM. NOW CUT THE CORD LENGTHS IN HALF SO YOU HAVE 40 LENGTHS OF CORD (MINE ARE AROUND 18CM EACH). THESE ARE YOUR WORKING CORDS





NOT TO SCALE BUT USE AS A GUIDE OR FREESTYLE




NOT TO SCALE BUT USE AS A GUIDE OR FREESTYLE

FOLD THE FILLER CORD IN HALF AND PIN THE END WITH THE LOOP UNDER THE CLIP



FOR EACH KNOT YOU WILL USE TWO SHORT WORKING CORDS (THE GREEN ONES IN THESE IMAGES)

NOW TAKE THE FIRST SHORT CORD (WORKING CORD) AND FOLD IN HALF



PLACE THIS
WORKING CORD
UNDER THE FILLER
CORDS WITH THE
LOOP ON THE
RIGHT



FOLD A SECOND WORKING CORD IN HALF AND TUCK THE OPEN ENDS THROUGH THE LOOP ON THE RIGHT (THIS SITS ON THE TOP OF THE FILLER CORDS)



NOW BRING THE END OF THE FIRST
WORKING CORD UP THROUGH THE LOOP
OF THE SECOND WORKING CORD



## GENTLE PULL THE WORKING CORDS OUT TO THE SIDES

BEFORE TIGHTENING COMPLETELY POSITION WHERE YOU WANT THE KNOT TO BE ON YOUR FILLER CORDS (LEAVE SOME SPACE TO HAVE A LOOP AT THE TOP TO HANG YOUR LEAF/ FEATHER)



REPEAT STEPS 2-6 UNTIL ALL YOUR CORDS HAVE GONE OR YOU HAVE THE DESIRED LENGTH YOU WISH. NOW SEPARATE OUT THE TWO FILLER CORDS (THE WHITE ONES IN THE IMAGE) AND TIE A KNOT TO SECURE ALL THE OTHER KNOTS IN PLACE

I FIND IT EASIER TO FRAY THE WORKING CORDS FIRST AND THEN CUT TO DESIRED SHAPE (YOU CAN DO IT THE OTHER WAY AROUND IF YOU LIKE)



IF YOU ARE USING SINGLE PLY THEN YOU CAN USUALLY BRUSH STRAIGHT AWAY. IF 4 PLY LIKE MINE THEN YOU WILL NEED TO UNTWIST STRANDS FIRST AND THEN BRUSH





ONCE YOU HAVE FRAYED OUT THE CORD USING A BRUSH/ COMB YOU CAN THEN CUT YOUR PROJECT TO YOUR DESIRED SHAPE